

Model: **LM-25**
Lensmeter



SHIN-NIPPON

SHIN-NIPPON

LENSMETER

Model: LM-25

Features

- **Unrestricted tilting angle;** can be clamped at any angle allowing measurement while in a comfortable position.
- **Full 90° tilting;** can be tilted to a full 90° for easy measurement of contact lenses.
- **Accepts large diameter lenses** (from 24–90mm)
- Uses crossline and corona target.
- Can be equipped with a prism compensator (optional)



Specifications

Vertex Power	Range	+25 diopters to -25 diopters
	Step	0.125 diopters up to ±3 diopters
		0.25 diopters beyond ±3 diopters
Prismatic Power	Range	5 prism diopters
	Step	0.5 diopters up to 2 diopters
		1 diopter beyond 2 diopters
Cylindrical Axis	Range	0 to 180 degrees
	Step	1 degree
Target Method	Corona crossline	
Lenses Accommodated	Diameter	24 to 90 mm
	Step	2 mm
Intervals of Lensholder	Pitch	16 mm
Tilting Angle	30 to 90 degrees	
Eyepiece Focusing	+7D to -10D	
Bulb	110V 15W	
Measurement	475(H)X130(W)X330(D) mm	
Net Weight	4.9 kg	
Standard Accessories	2 bulbs 1 Vinyl cover 1 Contact lens holder 1 Bifocal lens holder	
Optional Accessories	Prism compensator Diopter range : 15 diopters Graduations : 1 diopter step Angle scale : 0–180° Graduations : 5°	



Model: LM-25

Internal Reading System
Target: Crossline and Corona



Prism Compensator



Measurement of Contact Lens

Design and specifications are subject to change without notice.

AJINOMOTO®

AJINOMOTO TRADING, INC.

SHIN-NIPPON Medical & Ophthalmic Instruments Dept.

EAST WING 7F, TFT BUILDING, 3-1-22 ARIAKE, KOTO-KU,

TOKYO 135-8071, JAPAN

TEL: 813-3528-4416 FAX: 813-3528-4426

<http://www.shin-nippon.jp> <http://www.ajitrade.com>



Distributed by